



Standard Kiosk Thermal Printer **Presto KTP-602 Series**

Product Specification

| | | |
|--|---------------------------------------|---------------------------------------|
| ● Printer type | KTP-622-*X | KTP-632-*X |
| ● Operating power | 24VDC | 24VDC |
| ● Current peak | approx. 3,5A | approx. 3,5A |
| ● Paper insertion | rear | rear |
| ● Paper width | 2 inch/60mm | 3 inch/80mm |
| ● Eff. printing width | 56mm | 72mm |
| ● Printing speed | 100mm/sec. | 80mm/sec. |
| ● Paper thickness | 60-100ym | 60-100ym |
| ● Paper roll diameter | *X= 100/180/230mm | *X= 100/180mm |
| ● Operating temp. | -10°C to +40°C | -10°C to +40°C |
| ● Storage temp. | -20°C to +60°C | -20°C to +60°C |
| ● Head life | 30km | 30km |
| ● Head configuration | 448dots/line | 576dots/line |
| ● Cutter life time | 500.000 cuts | 500.000 cuts |
| ● Cutting type | full or partial | full or partial |
| ● Interface | RS232 & USB | RS232 & USB |
| ● Drivers: | Win98/2K/XP/CE, Linux, ASCII commands | Win98/2K/XP/CE, Linux, ASCII commands |
| ● Mech. dim. (WxDxH) | 95x160x125mm incl. 100mm paper roll | 118x160x125mm incl. 100mm paper roll |
| ● Paper auto feed detection, head up detection, black mark detection, head temperature detection | | |
| ● Paper near end sensor, paper end sensor | | |

Product Applications

- Kiosk
- ATM
- Ticketing
- Gaming
- Receipt

itp systems & solutions GmbH & Co.KG
Am Forst 6; D-85560 Ebersberg, Germany
Phone: +49/(0)8092/8510 877- Fax: +49/(0)8092/8511 740; e-mail: info@itpsyso.com ; www.itpsyso.com

YOUR SUCCESS IS OUR MOTIVATION