



Kiosk Thermal Printer 12V with Presenter **Presto KTP-609 Series**

Product Specification

● Printer type	KTP-629-*X-12V-P	KTP-639-00-*X-12V-P	KTP-639-01-*X-12V-P
● Operating power	12VDC	12VDC	12VDC
● Current peak	approx. 3,5A	approx. 3,5A	approx. 3,5A
● Paper insertion	rear	rear	rear
● Paper width	2 inch/60mm	3 inch/80mm	3 inch/82,5mm
● Eff. printing width	54mm	72mm	80mm
● Printing speed	100mm/sec.	100mm/sec.	100mm/sec.
● Paper thickness	80-120ym	80-120ym	80-120ym
● Paper roll diameter	*X= 100/180mm	*X= 100/180mm	*X= 100/180
● Operating temp.	-20°C to +60°C	-20°C to +60°C	- 20°C to +60°C
● Storage temp.	-20°C to +60°C	-20°C to +60°C	-20 °C to +60°C
● Head life	100km	100km	100km
● Head configuration	432dots/line	576dots/line	640dots/line
● Cutter life time	500.000 cuts at 80g	500.000 cuts at 80g	500.000 cuts at 80g
● Cutting type	full cut	full cut	full cut
● Interface	RS232	RS232	RS232
● Presenter	loop presenter	loop presenter	loop presenter
● Drivers:	Win98/2K/XP/CE, Linux, ASCII commands	Win98/2K/XP/CE, Linux, ASCII commands	Win98/2K/XP/CE, Linux, ASCII commands
● Mech. dim. (WxDxH)	105x221x125mm incl. 100mm paper roll	128x221x125mm incl. 100mm paper roll	128x221x125mm incl. 100mm paper roll
● Paper auto feed detection, head up detection, black mark detection, head temperature detection			
● Paper near end sensor, paper end sensor			

Product Applications

- Kiosk
- ATM
- Ticketing
- Gaming
- Receipt

itp systems & solutions GmbH & Co.KG
Am Forst 6; D-85560 Ebersberg, Germany
Phone: +49/(0)8092/8510 877- Fax: +49/(0)8092/8511 740; e-mail: info@itpsyso.com ; www.itpsyso.com

YOUR SUCCESS IS OUR MOTIVATION