



Easy Loading Panel Printer **Presto KTP-609-ELM Series**

Product Specification

● Printer type	KTP-629-ELM-12V	KTP-629-ELM
● Operating power	12VDC	24VDC
● Current peak	approx. 4,0A	approx. 4,0A
● Paper insertion	easy loading	easy loading
● Paper width	2 inch/58mm	2 inch/58mm
● Eff. printing width	54mm	54mm
● Printing speed	100mm/sec.	200mm/sec.
● Paper thickness	80-120ym	80-120ym
● Paper roll diameter	75mm	75mm
● Operating temp.	-20°C to +60°C	-20°C to +60°C
● Storage temp.	-20°C to +60°C	-20°C to +60°C
● Head life	100km	100km
● Head configuration	432dots/line	432dots/line
● Cutter life time	500.000 cuts at 80g	500.000 cuts at 80g
● Cutting type	full or partial	full or partial
● Interface	RS232 & USB	RS232 & USB
● Drivers:	Win98/2K/XP/CE, Linux, ASCII commands	Win98/2K/XP/CE, Linux, ASCII commands
● Mech. dim. (WxDxH)	114x85x150mm	114x85x150mm

● Paper auto feed detection, head up detection, black mark detection, head temperature detection

● Paper near end sensor, paper end sensor

Product Applications

- Kiosk
- ATM
- Ticketing
- Gaming
- Receipt

y

itp systems & solutions GmbH & Co.KG
Am Forst 6; D-85560 Ebersberg, Germany
Phone: +49/(0)8092/8510 877- Fax: +49/(0)8092/8511 740; e-mail: info@itpsyso.com ; www.itpsyso.com

YOUR SUCCESS IS OUR MOTIVATION