



High Speed Kiosk Thermal Printer Presto KTP-609 Series

Product Specification

| | | | |
|--|---------------------------------------|---------------------------------------|---------------------------------------|
| ● Printer type | KTP-629-*X | KTP-639-00-*X | KTP-639-01-*X |
| ● Operating power | 24VDC | 24VDC | 24VDC |
| ● Current peak | approx. 3,5A | approx. 3,5A | approx. 3,5A |
| ● Paper insertion | rear | rear | rear |
| ● Paper width | 2 inch/60mm | 3 inch/80mm | 3 inch/82,5mm |
| ● Eff. printing width | 54mm | 72mm | 80mm |
| ● Printing speed | 200mm/sec. | 200mm/sec. | 200mm/sec. |
| ● Paper thickness | 80-120ym | 80-120ym | 80-120ym |
| ● Paper roll diameter | *X= 100/180/230mm | *X= 100/180mm | *X= 100/180mm |
| ● Operating temp. | -20°C to +60°C | -20°C to +60°C | - 20°C to +60°C |
| ● Storage temp. | -20°C to +60°C | -20°C to +60°C | -20 °C to +60°C |
| ● Head life | 100km | 100km | 100km |
| ● Head configuration | 432dots/line | 576dots/line | 640dots/line |
| ● Cutter life time | 500.000 cuts at 80g | 500.000 cuts at 80g | 500.000 cuts at 80g |
| ● Cutting type | full or partial | full or partial | full or partial |
| ● Interface | RS232 & USB | RS232 &USB | RS232 &USB |
| ● Drivers: | Win98/2K/XP/CE, Linux, ASCII commands | Win98/2K/XP/CE, Linux, ASCII commands | Win98/2K/XP/CE, Linux, ASCII commands |
| ● Mech. dim. (WxDxH) | 95x160x125mm incl. 100mm paper roll | 118x160x125mm incl. 100mm paper roll | 118x160x125mm incl. 100mm paper roll |
| ● Paper auto feed detection, head up detection, black mark detection, head temperature detection | | | |
| ● Paper near end sensor, paper end sensor | | | |

Product Applications

- Kiosk
- ATM
- Ticketing
- Gaming
- Receipt

itp systems & solutions GmbH & Co.KG
Am Forst 6; D-85560 Ebersberg, Germany
Phone: +49/(0)8092/8510 877- Fax: +49/(0)8092/8511 740; e-mail: info@itpsyso.com ; www.itpsyso.com

YOUR SUCCESS IS OUR MOTIVATION