



## ITP-104 Touch PC

### Hardware Features

- Processor Intel XScale PXA270/PXA320 (32 Bit)  
312, 520 and 802 MHz
- Memory RAM 64 MB SDRAM (32 bit) for PXA270  
128 MB DDR (32 bit) for PXA320
- On-board flash 32 MB NOR flash (32 bit) for PXA270  
64 MB NAND flash (16 bit) for PXA320
- Power supply 8-16 VDC, 8W, optional power over Ethernet 18-30VDC
- Display 10.4 inch SVGA bright TFT, 4 wire touch screen, 800x600
- Inputs/outputs 1x RJ-45 for network  
2x USB ports 1.1 compliant (host/client)  
2x Serial UART (RS232)  
1x Audio line in/out stereo jack  
1x micro SD card slot
- Storage SD card memory, 32MB up to 4GB
- Environment 0°C ... 50°C operating temp.  
IP-65 standard
- Compact size 209x264x30mm

### Software Features

- Operating system Microsoft Windows CE5.0, real time OS, Linux solutions provided on request
- Supplied software Image flash updater, Web Server, File Server, Terminal Services Client, Internet Explorer, E-mail client, Wordpad, Media Player, PowerPoint/PDF file/Image Viewer
- Optional accessories desk stand, wall mount (VESA 75 standard), RJ48-DB9 adapter cable