



Fujitsu Standard Thermal Printer

FTP-622MCL001/002

FTP-632MCL001/002

Product Specification

● Printer type	FTP-622MCL001	FTP-622MCL002	FTP-632MCL001	FTP-632MCL002
● Operating power	24VDC	24VDC	24VDC	24VDC
● Current peak	approx. 2,3A	approx. 2,3A	approx. 2,3A	approx. 2,3A
● Paper insertion	front	rear	front	rear
● Paper width	58mm	60mm	80mm	85mm
● Eff. printing width	56mm	56mm	72mm	72mm
● Printing speed	80mm/sec.	80mm/sec.	80mm/sec.	80mm/sec.
● Paper thickness	60-100ym	60-100ym	60-100ym	60-100ym
● Operating temp.	-10°C to +40°C	-10°C to +40°C	-10°C to +40°C	-10°C to +40°C
● Storage temp.	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C
● Head life	50km	50km	50km	50km
● Head configuration	448dots/line	448dots/line	576dots/line	576dots/line
● Cutter life time	-	-	-	-
● Cutting type	-	-	-	-
● Mech. dim. (WxDxH)	82x48x20mm	82x48x20mm	108x48x20mm	108x48x20mm
● Paper auto feed detection, head up detection, black mark detection, head temperature detection				
● RS232/USB interface board available				

Product Applications

- Kiosk
- ATM
- Ticketing
- Label
- Receipt

itp systems & solutions GmbH & Co.KG
 Am Forst 6; D-85560 Ebersberg, Germany
 Phone: +49/(0)8092/8510 877- Fax: +49/(0)8092/8511 740; e-mail: info@itpsyso.com ; www.itpsyso.com

YOUR SUCCESS IS OUR MOTIVATION