



Fujitsu Standard Thermal Printer

FTP-622MCL303/304

FTP-632MCL303/304

Product Specification

● Printer type	FTP-622MCL303	FTP-622MCL304	FTP-632MCL303	FTP-632MCL304
● Operating power	24VDC	24VDC	24VDC	24VDC
● Current peak	approx. 2,3A	approx. 2,3A	approx. 2,3A	approx. 2,3A
● Paper insertion	front	rear	front	rear
● Paper width	58mm	60mm	80mm	85mm
● Eff. printing width	56mm	56mm	72mm	72mm
● Printing speed	80mm/sec.	80mm/sec.	80mm/sec.	80mm/sec.
● Paper thickness	60-100ym	60-100ym	60-100ym	60-100ym
● Operating temp.	-10°C to +40°C	-10°C to +40°C	-10°C to +40°C	-10°C to +40°C
● Storage temp.	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C
● Head life	50km	50km	50km	50km
● Head configuration	448dots/line	448dots/line	576dots/line	576dots/line
● Cutter life time	500.000 cuts at 60ym	500.000 cuts at 60ym	500.000 cuts at 60ym	500.000 cuts at 60ym
● Cutting type	full or partial	full or partial	full or partial	full or partial
● Mech. dim. (WxDxH)	96,7x56,5x37,7mm	96,7x56,5x37,7mm	116,9x56,5x37,7mm	116,9x56,5x37,7mm
● Paper auto feed detection, head up detection, black mark detection, head temperature detection				
● RS232/USB interface board available				

Product Applications

- Kiosk
- ATM
- Ticketing
- Label
- Receipt

itp systems & solutions GmbH & Co.KG
 Am Forst 6; D-85560 Ebersberg, Germany
 Phone: +49/(0)8092/8510 877- Fax: +49/(0)8092/8511 740; e-mail: info@itpsyso.com ; www.itpsyso.com

YOUR SUCCESS IS OUR MOTIVATION