



Fujitsu Miniature Easy Loading Thermal Printer **FTP-627MCL401/601** **FTP-637MCL401**

Product Specification

● printer type	FTP-627MCL401	FTP-627MCL601	FTP-637MCL401
● Operating power	24VDC	24VDC	24VDC
● Current peak	approx. 3,5A	approx. 3,5A	approx. 4,4A
● Paper insertion	easy loading	easy loading	easy loading
● Paper width	58mm	58mm	80mm
● Eff. printing width	48mm	48mm	72mm
● Printing speed	100mm/sec. max.	150mm/sec. max.	100mm/sec. max.
● Paper thickness	60ym	60ym	60ym
● Operating temp.	0°C to +50°C	0°C to +50°C	0°C to +50°C
● Storage temp.	20°C to +60°C	-20°C to +60°C	-20°C to +60°C
● Head life	50km	50km	50km
● Head configuration	384dots/line	384dots/line	576dots/line
● Cutter life time	500.000 cuts	500.000 cuts	500.000 cuts
● Cutting type	full or partial	full or partial	full or partial
● Mech. dim. (WxDxH)	81,2x42,2x21,8mm	81,2x42,2x21,8mm	103,2x42,2x21,8mm
● Paper detection, head up detection, black mark detection, head temperature detection			
● RS232/USB interface board available			

Product Applications

- Mobile
- ECR/Cash
- Hand held
- Receipt
- Ticketing

itp systems & solutions GmbH & Co.KG
 Am Forst 6; D-85560 Ebersberg, Germany
 Phone: +49/(0)8092/8510 877- Fax: +49/(0)8092/8511 740; e-mail: info@itpsyso.com ; www.itpsyso.com

YOUR SUCCESS IS OUR MOTIVATION