



Fujitsu Miniature Thermal Printer FTP-628MCL353

Product Specification

● Printer type	FTP-628MCL353 #01	FTP-628MCL353 #02	
● Operating power	4,2-8,5VDC	4,2-8,5VDC	
● Current peak	approx. 2,4A	approx. 2,4A	
● Paper insertion	front	front	
● Paper width	58mm	58mm	
● Eff. printing width	48mm	48mm	
● Printing speed	60mm/sec.	60mm/sec.	
● Paper thickness	60ym	60ym	
● Operating temp.	-20°C to +60°C	-20°C to +60°C	
● Storage temp.	-20°C to +60°C	-20°C to +60°C	
● Head life	50km	50km	
● Head configuration	384dots/line	384dots/line	
● Cutter life time	300.000 cuts	300.000 cuts	
● Cutting type	full cut	partial cut	
● Mech. dim. (WxDxH)	83,5x43,0x26,4mm	83,5x43,0x26,4mm	without lever
● Paper auto feed detection, head up detection, black mark detection, head temperature detection			
● RS232/USB interface board available			

Product Applications

- Mobile
- ECR/Cash
- Hand held
- Receipt

itp systems & solutions GmbH & Co.KG
Am Forst 6; D-85560 Ebersberg, Germany
Phone: +49/(0)8092/8510 877- Fax: +49/(0)8092/8511 740; e-mail: info@itpsyso.com ; www.itpsyso.com

YOUR SUCCESS IS OUR MOTIVATION