



Fujitsu Miniature Thermal Printer FTP-628MCL354

Product Specification

● printer type	FTP-628MCL354#01	FTP-628MCL354 #02
● Operating power	4,2-8,5VDC	4,2-8,5VDC
● Current peak	approx. 2,4A	approx. 2,4A
● Paper insertion	front	front
● Paper width	58mm	58mm
● Eff. printing width	48mm	48mm
● Printing speed	60mm/sec.	60mm/sec.
● Paper thickness	60ym	60ym
● Operating temp.	-20°C to +60°C	-20°C to +60°C
● Storage temp.	-20°C to +60°C	-20°C to +60°C
● Head life	50km	50km
● Head configuration	384dots/line	384dots/line
● Cutter life time	300.000 cuts	300.000 cuts
● Cutting type	full cut	partial cut
● Mech. dim. (WxDxH)	83,5x43,0x26,4mm	83,5x43,0x26,4mm
● Paper auto feed detection, head up detection, black mark detection, head temperature detection		
● RS232/USB interface board available		

Product Applications

- Mobile
- ECR/Cash
- Hand held
- Receipt

itp systems & solutions GmbH & Co.KG
Am Forst 6; D-85560 Ebersberg, Germany
Phone: +49/(0)8092/8510 877- Fax: +49/(0)8092/8511 740; e-mail: info@itpsyso.com ; www.itpsyso.com

YOUR SUCCESS IS OUR MOTIVATION