



# ***Fujitsu High Speed Thermal Printer*** **FTP-629MCL054** **FTP-639MCL054/064**

## **Product Specification**

● printer type	FTP-629MCL054	FTP-639MCL054	FTP-639MCL064
● operating power	24VDC	24VDC	24VDC
● current peak	approx. 3,0A	approx. 4,0A	approx. 5,6A
● paper insertion	rear	rear	rear
● paper width	60mm	80mm	82,5mm
● eff. printing width	54mm	72mm	80mm
● printing speed	200mm/sec.	200mm/sec.	200mm/sec.
● paper thickness	80-120ym	80-120ym	80-120ym
● operating temp.	-20°C to +60°C	-20°C to +60°C	-20 °C to +60°C
● storage temp.	-20°C to +60°C	-20°C to +60°C	-20° C to +60°C
● head life	50km	50km	50km
● head configuration	432dots/line	576dots/line	640dots/line
● cutter life time	-	-	-
● cutting type	-	-	-
● mech. dim. (WxDxH)	82,5x40,5x20,5mm	104,2x40,5x20,5mm	104,2x40,5x20,5mm
● paper auto feed detection, head up detection, black mark detection, head temperature detection			
● RS232/USB interface board available			

## **Product Applications**

- Kiosk
- ATM
- Ticketing
- Label
- Receipt

itp systems & solutions GmbH & Co.KG  
 Am Forst 6; D-85560 Ebersberg, Germany  
 Phone: +49/(0)8092/8510 877- Fax: +49/(0)8092/8511 740; e-mail: info@itpsyso.com ; www.itpsyso.com

***YOUR SUCCESS IS OUR MOTIVATION***