



Fujitsu High Speed ELM Thermal Printer

FTP-629MCL103

FTP-639MCL103

Product Specification

● printer type	FTP-629MCL103	FTP-639MCL103
● operating power	24VDC	24VDC
● current peak	approx. 3,0A	approx. 4,0A
● paper insertion	easy loading	easy loading
● paper width	58mm	80mm
● eff. printing width	54mm	72mm
● printing speed	200mm/sec.	200mm/sec.
● paper thickness	80-120ym	80-120ym
● operating temp.	-20°C to +60°C	-20°C to +60°C
● storage temp.	-20°C to +60°C	-20°C to +60°C
● head life	50km	50km
● head configuration	432dots/line	576dots/line
● cutter life time	-	-
● cutting type	-	-
● mech. dim. (WxDxH)	82,2x40,4x20,5mm	104,2x40,5x20,5mm
● paper detection, head up detection, black mark detection, head temperature detection		
● RS232/USB interface board available		

Product Applications

- Kiosk
- ATM
- Ticketing
- Label
- Receipt

itp systems & solutions GmbH & Co.KG
 Am Forst 6; D-85560 Ebersberg, Germany
 Phone: +49/(0)8092/8510 877- Fax: +49/(0)8092/8511 740; e-mail: info@itpsyso.com ; www.itpsyso.com

YOUR SUCCESS IS OUR MOTIVATION