



## ***Fujitsu High Speed Thermal Printer*** **FTP-629MCL354** **FTP-639MCL354**

### **Product Specification**

● Printer type	FTP-629MCL354	FTP-639MCL354	FTP-639MCL364
● Operating power	24VDC	24VDC	24VDC
● Current peak	approx. 3,0A	approx. 4,0A	approx. 5,6A
● Paper insertion	rear	rear	rear
● Paper width	60mm	80mm	82,5mm
● Eff. printing width	54mm	72mm	80mm
● Printing speed	200mm/sec.	200mm/sec.	200mm/sec.
● Paper thickness	80-120ym	80-120ym	80-120ym
● Operating temp.	-20°C to +60°C	-20°C to +60°C	-20 °C to +60°C
● Storage temp.	-20°C to +60°C	-20°C to +60°C	-20°C to +60°C
● Head life	50km	50km	50km
● Head configuration	432dots/line	576dots/line	640dots/line
● Cutter life time	500.000 cuts	500.000 cuts	500.000 cuts
● Cutting type	full or partial cut	full or partial cut	full or partial cut
● Mech. dim. (WxDxH)	90,6x62,5x37,7mm	109,5x62,5x37,7mm	109,5x62,5x37,7mm
● Paper auto feed detection, head up detection, black mark detection, head temperature detection			
● RS232/USB interface board available			

### **Product Applications**

- Kiosk
- ATM
- Ticketing
- Label
- Receipt

itp systems & solutions GmbH & Co.KG  
 Am Forst 6; D-85560 Ebersberg, Germany  
 Phone: +49/(0)8092/8510 877- Fax: +49/(0)8092/8511 740; e-mail: info@itpsyso.com ; www.itpsyso.com

***YOUR SUCCESS IS OUR MOTIVATION***