



Fujitsu 4 Wire Touch Panel

Product Specification

● Technology	flim/glass	conductive Polymer/glass	automotive film/glass
● Operating power	3,3 or 5VDC	3,3 or 5VDC	3,3 or 5VDC
● Transparency	80 to 82% standard	80% typical	82% to 90%
● Haze	5% typical	5 % typical	5% typical
● Hardness	3 H min.	3H	>3H
● Coating	anti glare standard	anti glare standard	anti glare standard
● Size	2" to 17.0"	2" to 7"	3,5" to 8"
● input	pen & finger	pen & finger	finger
● Writing life	100.000 touches	500.000 touches	1 million touches
● Knocking life	1 million touches	10 million touches	10 million touches
● Linearity	1,5% to 3,5%	1,5% to 3,5%	<1,5%
● Resolution	0,1mm	0,1mm	0,1mm
● Operating temp.	-2°C to +55°C	-10°C to +60°C	-3 0°C to +85°C
● Storage temp.	-30°C to +70°C	-30°C to +70°C	-40 °C to +95°C

Control Board/Control Chip

● Interface	RS232 or USB	RS232 or USB	RS232 or USB
● Board size LxW	75x30mm	75x30mm	75x30mm

Product Applications

- PDA
- ECR/Cash
- Kiosk
- Automotive
- Medical

itp systems & solutions GmbH & Co.KG
 Am Forst 6; D-85560 Ebersberg, Germany
 Phone: +49/(0)8092/8510 877- Fax: +49/(0)8092/8511 740; e-mail: info@itpsyso.com ; www.itpsyso.com

YOUR SUCCESS IS OUR MOTIVATION